



Features:

- Revolutionary new design that integrates LCD monitor and thin client into one sleek device.
- Fanless System for Noiseless Operation.
- Ultra Low Power Consumption.
- Supports a rich set of I/O and Peripherals.
- Linux-based Thin Client OS
 - **RDP, ICA** and **VNC** protocols for Remote Desktop connectivity to Windows XP and 7, Windows Server 2003 and 2008.
 - **X11, XDMCP** and VNC connectivity to Linux/UNIX.
 - SSH, Telnet, VT100 and VT220 terminal emulation.
 - **Web Browser** with PDF and Flash support, for cloud computing applications. Supports **VoIP** and chat.
 - Powerful **media player** for digital signage applications. Supports **H.264, MPEG2**, streaming, etc.



World's first and only x86 thin client integrated into an LCD monitor. Features industry lowest power consumption for an x86 thin client.

Hardware Specifications

Processor	1GHz x86 System-on-Chip Hardware graphics acceleration
Memory	DDR2 256 MB. Option for 512 MB.
Storage	2 GB Flash. Expandable upto 32 GB.
Display	Size 15.6" wide Resolution 1366 × 768 Response Time 8 ms Luminance 250 Cd/m ² Contrast Ratio 500:1 Colours 24 bit, 16.7 Million Pixel Pitch 0.252 mm
Viewing Angle	Horizontal 90° Vertical 65°
Networking	10/100Base-T Fast Ethernet 802.11b/g/n WLAN (Optional)
Sound	3.5 mm stereo jacks
I/O Ports	1 × RJ-45 with diagnostic LEDs 4 × USB 2 × Audio: Mic In/Speaker Out 1 × SD Card reader
Dimensions	374 × 304 × 190 mm (with base) 75mm VESA Mount
Security	Kensington security lock slot
Environment	Temperature 0 ~ 45°C Humidity 10 to 90% Voltage 100 ~ 240VAC, 50 Hz Power 18 W typical
Weight	2.8 Kg
Certification	Energy Star, CE

Launching
September
2010

