



Features:

- Revolutionary new design that integrates an LED backlit LCD monitor and a thin client into one sleek device.
- Fanless System for Noiseless Operation.
- **LED backlit** screen delivers vibrant colours. Integrated speakers complete the rich media experience.
- Supports a rich set of I/O and Peripherals.
- Linux-based Thin Client OS.
 - **RDP, ICA** and **VNC** protocols for Remote Desktop connectivity to Windows XP and 7, Windows Server 2003 and 2008.
 - **X11, XDMCP** and VNC connectivity to Linux/UNIX.
 - SSH, Telnet, VT100 and VT220 terminal emulation.
 - **Web Browser** with PDF and Flash support, for cloud computing applications. Supports **VoIP** and chat.
 - Powerful **media player** for digital signage applications. Supports **H.264, MPEG2**, streaming, etc.



World's first and only x86 thin client integrated into an LCD monitor. Provides ease of use, elegance and energy conservation.

Hardware Specifications

Processor	VIA Eden 400 MHz x86 processor VIA CN700 chipset with hardware 2D/3D graphics acceleration
Memory	DDR2 256 MB. Expandable upto 1 GB.
Storage	256 MB Flash. Expandable upto 8 GB.
Display	Size 18.5" wide Resolution 1366 × 768 Response Time 5 ms Luminance 250 Cd/m ² Contrast Ratio 1000:1 Colours 24 bit, 16.7 M Pixel Pitch 0.3 mm
Viewing Angle	Horizontal 160° Vertical 160°
Networking	10/100Base-T Fast Ethernet 802.11b/g/n WLAN (Optional)
Sound	2 × 1W internal speakers
I/O Ports	1 × RJ-45 with diagnostic LEDs 4 × USB 2.0 – 3 external, 1 internal 2 × Audio: Mic In/Speaker Out
Dimensions	463 × 358 × 186 mm (with base) 100mm VESA Mount
Security	Kensington security lock slot
Environment	Temperature 0 ~ 45°C Humidity 10 to 90% Voltage 100 ~ 240VAC, 50 Hz Power 25 W typical
Weight	3.5 Kg
Certification	Energy Star, RoHS

