



## Features:

- Thin client based Dumb Terminal for server based operation using both serial and network connectivity.
- **Crystal clear, high resolution display.**
- Terminal Emulation
  - VT100 and VT220 terminal emulation.
  - Network connectivity over Telnet and SSH.
  - Serial connectivity to terminal server. Supports multiple baud rates such as 9600, 38400, and 115200.
  - Railways UTS and PRS form download capability.
  - Full key mapping of VT-220 terminal.
- Features that can be enabled or disabled through the password protected local terminal setup menu:
  - Terminal answer back.
  - Programmable functional keys (including shift and control key combinations).
  - Remote accessibility and configuration through Ethernet connectivity.
  - USB and LAN port access.
- Printing support:
  - Bi-directional communication with Dot Matrix Printers.
  - Serial or parallel port printing (selectable).
  - ISCII (83, 88 and 91) printing.
  - Epson, TVSe, Printronics and MT-Lipi emulation.
  - Prints all Indian languages.
- Write protected firmware.
- Very low energy consumption.
- Convenience tools such as a calculator and calendar.



Specifications are subject to change without prior notice.

## Hardware Specifications

<b>Processor</b>	x86 Architecture
<b>Memory</b>	Expandable RAM
<b>Storage</b>	Expandable Flash
<b>Display</b>	Up to 1920 x 1440, 32-bit colour
<b>Networking</b>	10/100/1000 Mbps Ethernet Port 802.11 b/g/n WLAN (Optional) PPP dialup for GPRS, CDMA, 3G. PPPoE for ADSL. Supports all Indian ISPs and USB modems.
<b>I/O Ports</b>	1 x RJ-45 with diagnostic LEDs 4 x USB 2.0 1 x 15-pin VGA connector 1 x 9-pin serial 1 x 25-pin serial 1 x 25-pin parallel 1 x PS/2 Keyboard/Mouse 1 x Power Switch
<b>Diagnostics</b>	Power On/Off and HDD Activity LEDs.
<b>Power Input</b>	220 ~ 240 V AC
<b>Dimensions</b>	270 x 53 x 203 mm
<b>Operating Temperature</b>	0 ~ 35 °C
<b>Net Weight</b>	1.75 kg
<b>Gross Weight</b>	2.35 kg

