



## Features:

- Powerful, cost effective thin client for both standalone and server based operation.
- Linux based Thin Client OS – Thinix Embedded Linux.
- Firefox, Chrome and Opera **Web Browsers** with **PDF, Flash, Java** and multimedia plugins.



- Powerful **media player** for digital signage applications. Supports **H.264, MPEG2**, streaming, etc.
- Complete desktop experience – office suite, VoIP and chat client, video-conferencing, etc.



- **RDP, ICA** and **VNC** protocols for Remote Desktop connectivity to Windows XP and 7, Windows Server 2008 and 2012. Printer, disk and sound forwarding.



- **VDI** Support: Microsoft RemoteFX and HyperV, Citrix XenServer, VmWare View



- Support for all popular printers, scanners and multi-functionals. Both local and server based printing.
- Biometric and smart card based authentication.
- RFID, bar code scanner, magnetic stripe and thermal printer support for Point-of-Sale applications.
- Remote Management Suite with browser based administration from any computer. VNC Shadowing.
- Locally install and run your Windows, Java and .NET applications.
- Ships with the latest Linux kernel and GNU libraries.
- For a detailed list of software features, please view the [Thinix Feature List](#) on our website.



Compact product with full legacy port support. Suitable for POS and thin client.

## Hardware Specifications

<b>Processor</b>	Intel 2.41 GHz Dual Core or 2.00 GHz Quad Core processor Hardware graphics acceleration
<b>Memory</b>	2 GB. Expandable to 8 GB.
<b>Storage</b>	8 GB Flash. Expandable to 64 GB. Supports SATA 2.5" HDD.
<b>Display</b>	Up to 1920 × 1080, 32-bit colour
<b>Networking</b>	10/100/1000 Mbps Ethernet Port 802.11 b/g/n WLAN (Optional) PPP dialup for 4G
<b>I/O Ports</b>	1 × RJ-45 with diagnostic LEDs ⑥ 4 × USB 2.0 ⑤ 1 × USB 3.0 ④ 1 × 15-pin VGA connector ⑦ 1 × HDMI ⑧ 1 × PS/2 Keyboard ② 1 × PS/2 Mouse ③ 3 × 3.5mm Audio Jacks ⑨ 1 × Power Switch
<b>Optional Ports</b>	1 × 9-pin serial 1 × 25-pin serial 1 × 25-pin parallel
<b>Diagnostics</b>	Power On/Off and HDD Activity LEDs
<b>Power Input</b>	220 ~ 240 V AC
<b>Dimensions</b>	240 × 183 × 60 mm
<b>Operating Temperature</b>	0 ~ 35 °C
<b>Net Weight</b>	1.40 kg
<b>Gross Weight</b>	2.30 kg

