



## Thinvent Aero Mini PC

### Intel Core i3-1215U processor

6 core, up to 4.4 GHz, 10 MB cache

### Dual LAN

### 64GB DDR4 RAM (2 x 32GB)

### 1TB SSD

### No WiFi

### Thinux Embedded Linux

SKU: AERO-I3\_12L-32\_32-M1024-12\_5-X-THINUX-0



Unleash compact power for demanding environments.

Engineered for reliability where it matters most, the Thinvent® Aero Mini PC is the robust digital heart for your industrial applications. Its fanless, rugged design ensures silent, dust-resistant operation in control rooms, kiosks, and digital signage installations.

#### Why choose the Aero Mini PC

- Experience steadfast performance for 24/7 operations, thanks to efficient processing power that handles multiple tasks without faltering.

- Connect seamlessly to a wide array of peripherals and dual network lines, providing ultimate flexibility and redundancy for critical systems.
  - Deploy with confidence using the secure and stable Thinux™ platform, pre-loaded with essential tools for remote management, office tasks, and custom application support.
  - Simplify your setup and reduce cable clutter with a compact footprint that fits effortlessly into any workspace.
- Built to endure and designed to perform, it's the dependable computing solution that just works.



# Thinvent Aero Mini PC



## Specifications

### PROCESSING

|                 |         |
|-----------------|---------|
| Generation      | 12th    |
| Series          | i3      |
| Processor Brand | Intel   |
| Processor Model | 1215U   |
| Cores           | 6       |
| Max Frequency   | 4.4 GHz |
| Cache           | 10 MB   |
| Main Memory     | 64 GB   |
| SSD Storage     | 1024 GB |

### DISPLAY

|      |   |
|------|---|
| HDMI | 1 |
| VGA  | 1 |

### AUDIO

|                   |   |
|-------------------|---|
| Speaker Out       | 1 |
| Mic In            | 1 |
| Front Speaker Out | 1 |
| Front Mic In      | 1 |

### CONNECTIVITY

|               |   |
|---------------|---|
| USB 3.2       | 2 |
| Front USB 2.0 | 4 |
| Front USB C   | 1 |
| RS485 Option  | 1 |

### NETWORKING

|                |           |
|----------------|-----------|
| Ethernet       | 1000 Mbps |
| Ethernet Ports | 2         |

### POWER

|              |                                              |
|--------------|----------------------------------------------|
| DC Voltage   | 12 Volts                                     |
| DC Current   | 5 Amps                                       |
| Power Input  | 100~240 Volts AC, 50~60 Hz, 1.5 Amps maximum |
| Cable Length | 2 Metre                                      |

### ENVIRONMENTAL

|                       |                              |
|-----------------------|------------------------------|
| Operating Temperature | 0°C ~ 35°C                   |
| Operating Humidity    | 20% ~ 80% RH, non condensing |
| Certifications        | BIS, RoHS, ISO               |

### PHYSICAL

|                      |                       |
|----------------------|-----------------------|
| Form Factor          | Mini PC               |
| Dimensions           | 198mm × 187mm × 40mm  |
| Housing Material     | Steel and ABS Plastic |
| Housing Finish       | Powder Coated         |
| Housing Colour       | Black                 |
| Net and Gross Weight | 1.59kg, 1.59kg        |

### OPERATING SYSTEM

|                  |                                                                                                                                                                                                                                                                                                                                                                   |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating System | Thinvent® Thinux™ Embedded Linux                                                                                                                                                                                                                                                                                                                                  |
| OS Features      | <p>Chromium and Mozilla Firefox browsers.</p> <p>RDP 10 (RemoteFX, H.264/AVC), Putty and SSH for remote display.</p> <p>Browser based remote management. VNC shadowing.</p> <p>Java, Python and glibc based location application support.</p> <p>LibreOffice and PDF viewer.</p> <p>Multimedia player with MPEG4 support.</p> <p>SIP video and voice over IP.</p> |

## Ordering Information

## PRODUCT CODE

Aero-i3\_12l-[RAM]-[SSD]-12\_7-[Wireless]-[OS]-[Accessories]

## RAM

4 = 4GB DDR4

8 = 8GB DDR4

16 = 16GB DDR4

32 = 32GB DDR4

32\_32 = 64GB  
DDR4 RAM (2 x  
32GB)16\_16 = 32GB  
DDR4 RAM (2 x  
16GB)8\_8 = 16GB DDR4  
RAM (2 x 8GB)

## SSD

m128 = 128GB

m512 = 512GB

S32 = 32GB MLC

S256 = 256GB

m256 = 256GB

m1024 = 1TB

S128 = 128GB

## Wireless

m = Dual Band WiFi

X = No WiFi

## OS

DOS = DOS

11V = Windows 11 IoT Value

Thinix = Thinix™ Embedded Linux

W\_OS = Without OS

11P = Windows 11 Pro

U = Ubuntu Linux

## Accessories

0 = None

MK = Mechanical Keyboard

KM = Keyboard and Mouse set

Mo = Wired Optical Scroll Mouse

[www.thinvent.in](http://www.thinvent.in)[sales@thinvent.in](mailto:sales@thinvent.in)

+91-11-430-77467

 +91-99903-44251

## R&amp;D and Manufacturing

#11 Sports Complex

Salvador Do Mundo

North Goa - 403101, India

## Sales

UGF-10-A Omaxe Gurgaon Mall

Sector 49, Sohna Road

Gurgaon - 122018, India

