



Thinvent Neo H Mini PC

Intel Core i3-1215U processor

6 core, up to 4.4 GHz, 10 MB cache

Dual LAN

4GB DDR4 RAM

128GB SSD

Dual Band WiFi

Thinix Embedded Linux

DB9 Serial

SKU: H-I3_12L-4-M128-12_5-M-THINUX-1S



Engineered for relentless industrial performance, crafted in India.

The Neo H Mini PC: Built to power your most demanding industrial applications with unwavering reliability. This is the high-performance evolution of our bestselling Neo, delivering robust computing in a solid, compact form.

The powerhouse for industrial control

- Drive complex automation, machine interfacing, and process control systems with smooth, responsive power.
- Connect seamlessly to a vast array of legacy and modern equipment with dual LAN ports and serial connectivity.

- Deploy with absolute confidence in rugged environments, thanks to its solid steel construction and industrial-grade components.
- Simplify remote management and operation with the integrated Thinix™ platform, ready for specialised software and secure access.

Built to endure, designed to deliver. This is the industrial workhorse that just gets the job done, day in and day out.

Thinvent Neo H Mini PC



Specifications

PROCESSING

| | |
|-----------------|---------|
| Generation | 12th |
| Series | i3 |
| Processor Brand | Intel |
| Processor Model | 1215U |
| Cores | 6 |
| Max Frequency | 4.4 GHz |
| Cache | 10 MB |
| Main Memory | 4 GB |
| SSD Storage | 128 GB |

DISPLAY

| | |
|------|---|
| HDMI | 1 |
| VGA | 1 |

AUDIO

| | |
|-------------|---|
| Speaker Out | 1 |
| Mic In | 1 |

CONNECTIVITY

| | |
|--------------|------------------|
| USB 3.2 | 2 |
| Serial Port | 1 DB9 male RS232 |
| RS485 Option | 1 |

NETWORKING

| | |
|---------------------|-------------------------------|
| Ethernet | 1000 Mbps |
| Ethernet Ports | 2 |
| Wireless Networking | Wi-Fi 5 (802.11ac), dual band |

POWER

| | |
|--------------|--|
| DC Voltage | 12 Volts |
| DC Current | 5 Amps |
| Power Input | 100~240 Volts AC, 50~60 Hz, 1.5 Amps maximum |
| Cable Length | 2 Metre |

ENVIRONMENTAL

| | |
|-----------------------|------------------------------|
| Operating Temperature | 0°C ~ 40°C |
| Operating Humidity | 20% ~ 80% RH, non condensing |
| Certifications | BIS, RoHS, ISO |

PHYSICAL

| | |
|----------------------|-----------------------|
| Form Factor | Mini PC |
| Dimensions | 210mm × 202mm × 80mm |
| Packing Dimensions | 340mm × 235mm × 105mm |
| Housing Material | Steel |
| Housing Finish | Powder Coated |
| Housing Colour | Black |
| Net and Gross Weight | 1.69kg, 2.11kg |

OPERATING SYSTEM

| | |
|------------------|--|
| Operating System | Thinvent® Thinux™ Embedded Linux |
| OS Features | Chromium and Mozilla Firefox browsers. RDP 10 (RemoteFX, H.264/AVC), Putty and SSH for remote display. Browser based remote management. VNC shadowing. Java, Python and glibc based location application support. LibreOffice and PDF viewer. Multimedia player with MPEG4 support. SIP video and voice over IP. |

Ordering Information

| PRODUCT CODE | |
|--|--|
| H-i3_12l-[RAM]-[SSD]-12_7-[Wireless]-[OS]-[Accessories] | |
| RAM | 4 = 4GB DDR4 8 = 8GB DDR4 16 = 16GB DDR4 32 = 32GB DDR4 64 = 64GB DDR4 |
| SSD | m128 = 128GB m256 = 256GB m32 = 32GB m512 = 512GB m1024 = 1TB S32 = 32GB MLC S128 = 128GB S256 = 256GB |
| Wireless | m = Dual Band WiFi X = No WiFi |
| OS | DOS = DOS W_OS = Without OS 11V = Windows 11 IoT Value 11P = Windows 11 Pro Thinix = Thinix™ Embedded Linux U = Ubuntu Linux |
| Accessories | 0 = None KM = Keyboard and Mouse set 1S = DB9 Serial MK = Mechanical Keyboard Mo = Wired Optical Scroll Mouse |

www.thinvent.in

sales@thinvent.in

+91-11-430-77467

 +91-99903-44251

R&D and Manufacturing
 #11 Sports Complex
 Salvador Do Mundo
 North Goa - 403101, India

Sales
 UGF-10-A Omaxe Gurgaon Mall
 Sector 49, Sohna Road
 Gurgaon - 122018, India

