



# Thinvent Neo H Mini PC

## Intel Core i7-1255U processor

10 core, up to 4.7 GHz, 12 MB cache

## Dual LAN

## 4GB DDR4 RAM

## 256GB SSD

## No WiFi

## Thinux Embedded Linux

SKU: H-I7\_12L-4-M256-12\_5-X-THINUX-0



Engineered for relentless industrial performance.

Built to power the most demanding applications, the Thinvent® Neo H Mini PC is the ultimate industrial workhorse. This high-performance powerhouse delivers unwavering reliability where it matters most.

### Industrial Strength Reliability

- Rugged solid steel construction ensures durability in harsh environments.
- 100% designed and made in India for robust quality and support.
- Stable operation within a wide range of temperatures and humidity.

### Unmatched Connectivity and Control

- Dual Gigabit Ethernet ports for critical network redundancy and industrial networking.
- A host of legacy and modern ports for seamless integration with a vast array of industrial equipment.

- Ideal for machine control, automation, digital signage, and complex process management.

### Simplified, Secure Operation

- Runs the efficient Thinux™ Embedded Linux OS for stable, long-term performance without bloat.
- Features built-in remote management and VNC shadowing for easy maintenance and monitoring from anywhere.
- Pre-loaded with essential tools for development, office tasks, and multimedia, ready for your specific application.

Choose the industrial-grade computing solution that won't let you down. Deploy the Neo H for critical operations where power, connectivity, and absolute reliability are non-negotiable.



# Thinvent Neo H Mini PC



## Specifications

### PROCESSING

|                 |         |
|-----------------|---------|
| Generation      | 12th    |
| Series          | i7      |
| Processor Brand | Intel   |
| Processor Model | 1255U   |
| Cores           | 10      |
| Max Frequency   | 4.7 GHz |
| Cache           | 12 MB   |
| Main Memory     | 4 GB    |
| SSD Storage     | 256 GB  |

### DISPLAY

|      |   |
|------|---|
| HDMI | 1 |
| VGA  | 1 |

### AUDIO

|             |   |
|-------------|---|
| Speaker Out | 1 |
| Mic In      | 1 |

### CONNECTIVITY

|              |   |
|--------------|---|
| USB 3.2      | 2 |
| RS485 Option | 1 |

### NETWORKING

|                |           |
|----------------|-----------|
| Ethernet       | 1000 Mbps |
| Ethernet Ports | 2         |

### POWER

|              |                                              |
|--------------|----------------------------------------------|
| DC Voltage   | 12 Volts                                     |
| DC Current   | 5 Amps                                       |
| Power Input  | 100~240 Volts AC, 50~60 Hz, 1.5 Amps maximum |
| Cable Length | 2 Metre                                      |

### ENVIRONMENTAL

|                       |                              |
|-----------------------|------------------------------|
| Operating Temperature | 0°C ~ 40°C                   |
| Operating Humidity    | 20% ~ 80% RH, non condensing |
| Certifications        | BIS, RoHS, ISO               |

### PHYSICAL

|                      |                       |
|----------------------|-----------------------|
| Form Factor          | Mini PC               |
| Dimensions           | 210mm × 202mm × 80mm  |
| Packing Dimensions   | 340mm × 235mm × 105mm |
| Housing Material     | Steel                 |
| Housing Finish       | Powder Coated         |
| Housing Colour       | Black                 |
| Net and Gross Weight | 1.73kg, 2.14kg        |

### OPERATING SYSTEM

|                  |                                                                                                                                                                                                                                                                                                                                                                   |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating System | Thinvent® Thinux™ Embedded Linux                                                                                                                                                                                                                                                                                                                                  |
| OS Features      | <p>Chromium and Mozilla Firefox browsers.</p> <p>RDP 10 (RemoteFX, H.264/AVC), Putty and SSH for remote display.</p> <p>Browser based remote management. VNC shadowing.</p> <p>Java, Python and glibc based location application support.</p> <p>LibreOffice and PDF viewer.</p> <p>Multimedia player with MPEG4 support.</p> <p>SIP video and voice over IP.</p> |

## Ordering Information

## PRODUCT CODE

H-i7\_12l-[RAM]-[SSD]-12\_7-[Wireless]-[OS]-[Accessories]

## RAM

4 = 4GB DDR4

8 = 8GB DDR4

16 = 16GB DDR4

32 = 32GB DDR4

32\_32 = 64GB  
DDR4 RAM (2 x  
32GB)16\_16 = 32GB  
DDR4 RAM (2 x  
16GB)8\_8 = 16GB DDR4  
RAM (2 x 8GB)

## SSD

m128 = 128GB

m512 = 512GB

S32 = 32GB MLC

S256 = 256GB

m256 = 256GB

m1024 = 1TB

S128 = 128GB

## Wireless

m = Dual Band WiFi

X = No WiFi

## OS

DOS = DOS

11V = Windows 11 IoT Value

Thinix = Thinix™ Embedded Linux

W\_OS = Without OS

11P = Windows 11 Pro

U = Ubuntu Linux

## Accessories

0 = None

1S = DB9 Serial

Mo = Wired Optical Scroll Mouse

KM = Keyboard and Mouse set

MK = Mechanical Keyboard

[www.thinvent.in](http://www.thinvent.in)[sales@thinvent.in](mailto:sales@thinvent.in)

+91-11-430-77467

 +91-99903-44251

## R&amp;D and Manufacturing

#11 Sports Complex

Salvador Do Mundo

North Goa - 403101, India

## Sales

UGF-10-A Omaxe Gurgaon Mall

Sector 49, Sohna Road

Gurgaon - 122018, India

