



Thinvent Industrial PC IPC1

Intel processor N95

4 core, up to 3.4 GHz, 6 MB cache

64GB DDR4 RAM

128GB SSD

No WiFi

Thinux Embedded Linux

Thinvent Keyboard and Mouse set



SKU: IPC1-95-64-M128-12_5-X-THINUX-KM

Engineered for endurance, built for business.

Your reliable partner for demanding digital environments, the Thinvent Industrial PC IPC1 delivers unwavering performance where it matters most. Crafted from solid aluminium with a distinctive finned design, it dissipates heat efficiently for cool, consistent operation without the noise or dust of a fan. This robust, silent workhorse is 100% designed in India to thrive in both office and industrial settings.

Uncompromising reliability for critical operations

- Experience flawless, silent operation in sensitive environments like reception areas, control rooms, and quiet offices.

- Enjoy robust, maintenance-free performance thanks to its fanless, dust-resistant construction and durable aluminium chassis.
- Deploy with ultimate flexibility using the integrated VESA mount, fitting seamlessly behind monitors or in compact spaces.
- Leverage powerful remote management and a suite of pre-installed productivity software for effortless integration and control.
- Trust in a solution built for longevity, designed to deliver day-in, day-out without interruption.

Choose the IPC1 for a computing foundation that is as tough as it is quiet.



Specifications

PROCESSING

| | |
|-----------------|---------|
| Generation | 12th |
| Series | N |
| Processor Brand | Intel |
| Processor Model | N95 |
| Cores | 4 |
| Max Frequency | 3.4 GHz |
| Cache | 6 MB |
| Main Memory | 64 GB |
| SSD Storage | 128 GB |

DISPLAY

| | |
|------|---|
| HDMI | 1 |
| VGA | 1 |

AUDIO

| | |
|-------------------|---|
| Speaker Out | 1 |
| Mic In | 1 |
| Front Speaker Out | 1 |
| Front Mic In | 1 |

CONNECTIVITY

| | |
|---------------|---|
| USB 3.0 | 2 |
| Front USB 2.0 | 3 |

NETWORKING

| | |
|----------|-----------|
| Ethernet | 1000 Mbps |
|----------|-----------|

POWER

| | |
|--------------|--|
| DC Voltage | 12 Volts |
| DC Current | 5 Amps |
| Power Input | 100~240 Volts AC, 50~60 Hz, 1.5 Amps maximum |
| Cable Length | 2 Metre |

ENVIRONMENTAL

| | |
|-----------------------|------------------------------|
| Operating Temperature | 0°C ~ 40°C |
| Operating Humidity | 20% ~ 80% RH, non condensing |

PHYSICAL

| | |
|----------------------|------------------------------------|
| Form Factor | Industrial PC |
| Thermal Design | Fanless Passive Cooling |
| Dimensions | 199.5mm × 181.5mm × 34.5mm |
| Packing Dimensions | 340mm × 235mm × 105mm |
| Housing Material | Aluminium |
| Housing Finish | Powder Coated Base, Anodised Cover |
| Housing Colour | Black |
| Net and Gross Weight | 1.79kg, 2.21kg |

ACCESSORIES

| | |
|--------------------|---|
| Keyboard and Mouse | 1 |
| VESA Mount | 1 |

OPERATING SYSTEM

| | |
|------------------|--|
| Operating System | Thinvent® Thinux™ Embedded Linux |
| OS Features | Chromium and Mozilla Firefox browsers. RDP 10 (RemoteFX, H.264/AVC), Putty and SSH for remote display. Browser based remote management. VNC shadowing. Java, Python and glibc based location application support. LibreOffice and PDF viewer. Multimedia player with MPEG4 support. SIP video and voice over IP. |

Ordering Information

| PRODUCT CODE | |
|---|--|
| IPC1-95-[RAM]-[SSD]-12_5-[Wireless]-[OS]-[Accessories] | |
| RAM | 4 = 4GB DDR4 8 = 8GB DDR4 16 = 16GB DDR4 32 = 32GB DDR4 64 = 64GB DDR4 |
| SSD | m128 = 128GB m256 = 256GB m32 = 32GB m512 = 512GB m1024 = 1TB |
| Wireless | m = Dual Band WiFi X = No WiFi |
| OS | DOS = DOS W_OS = Without OS 11I = Windows 11 IoT 11P = Windows 11 Pro Thinux = Thinux™ Embedded Linux U = Ubuntu Linux |
| Accessories | 0 = None KM = Keyboard and Mouse set MK = Mechanical Keyboard Mo = Wired Optical Scroll Mouse |

www.thinvent.in

sales@thinvent.in

+91-11-430-77467

 +91-99903-44251

R&D and Manufacturing

#11 Sports Complex

Salvador Do Mundo

North Goa - 403101, India

Sales

UGF-10-A Omaxe Gurgaon Mall

Sector 49, Sohna Road

Gurgaon - 122018, India

