



Thinvent Industrial PC IPC3

Intel Core i3-1215U processor

6 core, up to 4.4 GHz, 10 MB cache

64GB DDR4 RAM

128GB SSD

Dual Band WiFi

DOS

Quad DB9 Serial



SKU: IPC3-I3_12-64-M128-12_5-M-DOS-4S

Unleash Unrivalled Performance in Any Environment.


Experience the pinnacle of industrial computing with the Thinvent® Industrial PC IPC3. 100% designed in India, this rugged, fanless powerhouse is engineered for relentless 24x7 operation in the harshest industrial and IoT environments. Its durable, anodised silver aluminium housing ensures silent, dust-free performance, making it the ultimate solution for critical applications requiring exceptional endurance.

Under the hood, the IPC3 boasts an Intel® Core™ i3-1215U processor with 6 cores and speeds up to 4.4 GHz, backed by a 10 MB cache. Paired with 4GB DDR4 RAM and a swift 256GB SSD, it delivers exceptional responsiveness and reliable processing power for demanding tasks. Designed to thrive, it operates flawlessly from 0°C to 50°C and maintains stability in high humidity.

Connectivity

- Extensive Serial Ports: 6 DB9 male RS232 for legacy and industrial devices.
- High-Speed USB: 2x USB 3.2, 2x USB 2.0 (rear), plus 4x Front USB 2.0 for versatile peripheral support.
- Flexible Display Outputs: 1x HDMI, 1x VGA.
- Robust Networking: 1000 Mbps Ethernet and dual-band Wi-Fi 5 (802.11ac).

Compact yet feature-rich, the IPC3 measures just 200mm × 184mm × 52mm, ensuring easy integration. With FreeDOS pre-installed and certified RoHS and ISO, it offers both flexibility and peace of mind. Powering your operations with precision and unparalleled endurance.



Specifications

PROCESSING

Generation	12th
Series	i3
Processor Brand	Intel
Processor Model	1215U
Cores	6
Max Frequency	4.4 GHz
Cache	10 MB
Main Memory	64 GB
SSD Storage	128 GB

DISPLAY

HDMI	1
VGA	1

AUDIO

Speaker Out	1
Mic In	1

CONNECTIVITY

USB 3.2	2
USB 2.0	2
Front USB 2.0	4
Front Serial Port	2 DB9 male RS232
Rear Serial Port	4 DB9 male RS232
RS485 Option	1

NETWORKING

Ethernet	1000 Mbps
Wireless Networking	Wi-Fi 5 (802.11ac), dual band

POWER

DC Voltage	12 Volts
DC Current	5 Amps
Power Input	100~240 Volts AC, 50~60 Hz, 1.5 Amps maximum
Cable Length	2 Metre

ENVIRONMENTAL

Operating Temperature	0°C ~ 50°C
Operating Humidity	20% ~ 80% RH, non condensing
Certifications	RoHS, ISO

PHYSICAL

Form Factor	Industrial PC
Thermal Design	Fanless Passive Cooling
Dimensions	200mm × 184mm × 52mm
Packing Dimensions	340mm × 235mm × 105mm
Housing Material	Aluminium
Housing Finish	Anodised
Housing Colour	Silver
Net and Gross Weight	2.45kg, 2.87kg

OPERATING SYSTEM

Operating System	FreeDOS
------------------	---------

Ordering Information

PRODUCT CODE				
IPC3-i3_12-[RAM]-[SSD]-12_7-[Wireless]-[OS]-[Accessories]				
RAM	4 = 4GB DDR4	8 = 8GB DDR4	16 = 16GB DDR4	32 = 32GB DDR4
	64 = 64GB DDR4			
SSD	m128 = 128GB		m256 = 256GB	
	m32 = 32GB		m512 = 512GB	
	m1024 = 1TB			
Wireless	m = Dual Band WiFi		X = No WiFi	
OS	DOS = DOS		W_OS = Without OS	
	11V = Windows 11 IoT Value		11P = Windows 11 Pro	
	Thinux = Thinux™ Embedded Linux		U = Ubuntu Linux	
Accessories	0 = None		4S = Quad DB9 Serial	

www.thinvent.in

sales@thinvent.in

+91-11-430-77467

 +91-99903-44251

R&D and Manufacturing

#11 Sports Complex

Salvador Do Mundo

North Goa - 403101, India

Sales

UGF-10-A Omaxe Gurgaon Mall

Sector 49, Sohna Road

Gurgaon - 122018, India

