



Thinvent Industrial PC IPC3

Intel Core i3-1215U processor

6 core, up to 4.4 GHz, 10 MB cache

Dual LAN

16GB DDR4 RAM (2 x 8GB)

512GB SSD

Dual Band WiFi

Thinux Embedded Linux

Quad DB9 Serial



SKU: IPC3-I3_12L-8_8-M512-12_5-M-THINUX-4S

Engineered for the relentless rhythm of industry.

Built to Endure


This isn't just a computer; it's a steadfast partner for your most demanding environments. Its fanless, rugged aluminium chassis shrugs off dust, vibration, and extreme temperatures, delivering flawless 24/7 operation where ordinary PCs would fail. Proudly 100% designed in India for robust performance.

Always Connected, Always in Control

Seamlessly integrate into any setup. With dual LAN ports, quad serial connections for legacy equipment, and built-in WiFi, it bridges the gap between new and old systems. Remotely manage and monitor operations from anywhere with our powerful browser-based tools, keeping your processes running smoothly without constant on-site presence.

The Heart of Your Smart Operations

Powered by our dedicated Thinux™ Embedded Linux OS, it's the perfect core for industrial automation, IoT gateways, and digital signage. Run custom applications, manage multimedia content, or handle complex data acquisition—all with reliable, silent efficiency. It's the dependable intelligence you need to drive productivity and innovation on the factory floor and beyond.



Specifications

PROCESSING

Generation	12th
Series	i3
Processor Brand	Intel
Processor Model	1215U
Cores	6
Max Frequency	4.4 GHz
Cache	10 MB
Main Memory	16 GB
SSD Storage	512 GB

DISPLAY

HDMI	1
VGA	1

AUDIO

Speaker Out	1
Mic In	1

CONNECTIVITY

USB 3.2	2
Front USB 2.0	4
Front Serial Port	2 DB9 male RS232
Rear Serial Port	4 DB9 male RS232
RS485 Option	1

NETWORKING

Ethernet	1000 Mbps
Ethernet Ports	2
Wireless Networking	Wi-Fi 5 (802.11ac), dual band

POWER

DC Voltage	12 Volts
DC Current	5 Amps
Power Input	100~240 Volts AC, 50~60 Hz, 1.5 Amps maximum
Cable Length	2 Metre

ENVIRONMENTAL

Operating Temperature	0°C ~ 50°C
Operating Humidity	20% ~ 80% RH, non condensing
Certifications	RoHS, ISO

PHYSICAL

Form Factor	Industrial PC
Thermal Design	Fanless Passive Cooling
Dimensions	200mm × 184mm × 52mm
Packing Dimensions	340mm × 235mm × 105mm
Housing Material	Aluminium
Housing Finish	Anodised
Housing Colour	Silver
Net and Gross Weight	2.45kg, 2.87kg

OPERATING SYSTEM

Operating System	Thinvent® Thinux™ Embedded Linux
OS Features	Chromium and Mozilla Firefox browsers. RDP 10 (RemoteFX, H.264/AVC), Putty and SSH for remote display. Browser based remote management. VNC shadowing. Java, Python and glibc based location application support. LibreOffice and PDF viewer. Multimedia player with MPEG4 support. SIP video and voice over IP.

Ordering Information

PRODUCT CODE				
IPC3-i3_12l-[RAM]-[SSD]-12_7-[Wireless]-[OS]-[Accessories]				
RAM	4 = 4GB DDR4	8 = 8GB DDR4	16 = 16GB DDR4	32 = 32GB DDR4
	32_32 = 64GB DDR4 RAM (2 x 32GB)	16_16 = 32GB DDR4 RAM (2 x 16GB)	8_8 = 16GB DDR4 RAM (2 x 8GB)	
SSD	m128 = 128GB	m256 = 256GB	m512 = 512GB	m1024 = 1TB
Wireless	m = Dual Band WiFi	X = No WiFi		
OS	DOS = DOS	W_OS = Without OS	11V = Windows 11 IoT Value	11P = Windows 11 Pro
	Thinix = Thinix™ Embedded Linux	U = Ubuntu Linux		
Accessories	0 = None	4S = Quad DB9 Serial		

www.thinvent.in

sales@thinvent.in

+91-11-430-77467

 +91-99903-44251

R&D and Manufacturing

#11 Sports Complex

Salvador Do Mundo

North Goa - 403101, India

Sales

UGF-10-A Omaxe Gurgaon Mall

Sector 49, Sohna Road

Gurgaon - 122018, India

