



Thinvent® Neo S Thin Client, Intel® processor N100 (4 core, up to 3.4 GHz, 6 MB cache), 16GB DDR4 RAM, 32GB SSD + 32 GB MLC SSD, 12V 2A Adapter, No WiFi, Thinux™ Embedded Linux, Thinvent® Keyboard and Mouse set

SKU: N-100-16-m32\_S32-12\_2-X-Thinux-KM

Unleash Power, Embrace Simplicity: The Thinvent® Neo S Thin Client



#### Processing

Cores	4
Max Frequency	3.4 GHz
Cache	6 MB
Main Memory	16 GB
SSD Storage	32 GB

#### Display

HDMI	1
VGA	1

#### Audio

Speaker Out	1
Mic In	1

#### Connectivity

USB 3.2 Gen 2	2
USB 3.2 Gen 1	1
USB C	1
Front USB 2.0	4
Serial Port	2 DB9 male RS232
Parallel Port	1 DB25 female IEEE 1284

#### Networking

Ethernet	1000 Mbps
<b>Power</b>	
DC Voltage	12 Volts
DC Current	2 Amps
Power Input	100~240 Volts AC, 50~60 Hz, 0.9 Amps maximum
Cable Length	1 Metre

#### Environmental

Operating Temperature	0°C ~ 40°C
Operating Humidity	20% ~ 80% RH, non condensing
Certifications	RoHS, ISO

#### Physical

Dimensions	196mm x 213mm x 27mm
Packing Dimensions	340mm x 235mm x 105mm
Housing Material	Aluminium
Housing Finish	Power Coating
Housing Colour	Black
Net and Gross Weight	1.22kg, 1.64kg

#### Accessories

Keyboard and Mouse	1
--------------------	---

#### Operating System

Operating System	Thinvent® Thinux™ Embedded Linux
OS Features	Chromium and Mozilla Firefox browsers. RDP 10 (RemoteFX, H.264/AVC), Putty and SSH for remote display.
	Browser based remote management. VNC shadowing.
	Java, Python and glibc based location application support.
	LibreOffice and PDF viewer.
	Multimedia player with MPEG4 support.
	SIP video and voice over IP.

