

Thinvent® Micro 6 Pro Mini PC, ARM® Cortex A55 processor (4 core, up to 1.9 GHz, 1 MB cache), 4GB Onboard RAM, 64GB eMMC Storage, 5V 2A Adapter, Dual Antenna WiFi, Thinux™ Embedded Linux, **VESA Mount for Micro**

SKU: P-6P-o4-e64-5_2P-D-Thinux-M

Power in Your Palm: Silent, Secure, and Made for Tomorrow.









_					
u	rn	r	CC	ın	\sim
г	ıv	-c	SS		u

Networking Ethernet

Wireless

Networking

Trocessing		
Cores	4	
Max Frequency	1.9 GHz	
Cache	1 MB	
Main Memory	4 GB	
SSD Storage	64 GB	
Display		
HDMI	1	
Audio		
Speaker Out	1	
Connectivity		
USB 3.0	1	
USB 2.0	1	
microSD Slot	1	

100 Mbps

Power

DC Voltage	5 Volts
DC Current	2 Amps
Power Input	100~275 Volts AC, 50~60 Hz, 2 Amps maximum
Power Consumption	7 Watts maximum
Cable Length	1.7 Metre

Environmental

Operating Temperature	0°C ~ 40°C
Operating Humidity	20% ~ 80% RH, non condensing
Certifications	BIS, RoHS, ISO

Physical

Dimensions	102mm × 90mm × 21mm	
Housing Material	Aluminium	
Housing Finish	Anodised	
Housing Colour	Dark Grey	

Accessories

VESA Mount

Operating System		
	Operating System	Thinvent® Thinux™ Embedded Linux
O	OS Features	Chromium and Mozilla Firefox browsers.
		RDP 10 (RemoteFX, H.264/AVC), Putty and SSH for remote display.
		Browser based remote management. VNC shadowing.
		Java, Python and glibc based location application support.
		LibreOffice and PDF viewer.
		Multimedia player with MPEG4 support.
		SIP video and voice over IP.



Wi-Fi, dual antenna, dual band