



# Thinvent Neo R/4 Mini PC

## Intel Core i3-1215U processor

6 core, up to 4.4 GHz, 10 MB cache

## Dual LAN

32GB DDR4 RAM (2 x 16GB)

128GB SSD

No WiFi

Thinux Embedded Linux

SKU: R-I3\_12L-16\_16-M128-12\_5-X-THINUX-0



Power your digital signage, kiosk, or IoT hub with reliable, silent computing.

Engineered for continuous operation in business-critical environments, the Thinvent® Neo R/4 delivers steadfast performance without the bulk or noise of a traditional desktop. It's the robust, compact core for your dedicated applications.

### Built for purpose

- Experience smooth, responsive operation for digital signage, interactive kiosks, and information displays.
- Depend on rock-solid stability with a fanless, industrial-grade steel chassis designed for 24/7 use.

- Simplify network integration and deployment with dual Gigabit Ethernet ports for flexible connectivity.
- Leverage the integrated Thinux™ OS, a secure and managed platform ready for remote administration and custom application support.
- Reduce your total cost of ownership with an energy-efficient design that saves on power and space.

The Neo R/4 is your dedicated workhorse. It just works, day in and day out, letting you focus on your business, not your hardware.



# Thinvent Neo R/4 Mini PC



## Specifications

### PROCESSING

|                 |         |
|-----------------|---------|
| Generation      | 12th    |
| Series          | i3      |
| Processor Brand | Intel   |
| Processor Model | 1215U   |
| Cores           | 6       |
| Max Frequency   | 4.4 GHz |
| Cache           | 10 MB   |
| Main Memory     | 32 GB   |
| SSD Storage     | 128 GB  |

### DISPLAY

|      |   |
|------|---|
| HDMI | 1 |
| VGA  | 1 |

### AUDIO

|             |   |
|-------------|---|
| Speaker Out | 1 |
| Mic In      | 1 |

### CONNECTIVITY

|              |   |
|--------------|---|
| USB 3.2      | 2 |
| RS485 Option | 1 |

### NETWORKING

|                |           |
|----------------|-----------|
| Ethernet       | 1000 Mbps |
| Ethernet Ports | 2         |

### POWER

|              |                                              |
|--------------|----------------------------------------------|
| DC Voltage   | 12 Volts                                     |
| DC Current   | 5 Amps                                       |
| Power Input  | 100~240 Volts AC, 50~60 Hz, 1.5 Amps maximum |
| Cable Length | 2 Metre                                      |

### ENVIRONMENTAL

|                       |                              |
|-----------------------|------------------------------|
| Operating Temperature | 0°C ~ 40°C                   |
| Operating Humidity    | 20% ~ 80% RH, non condensing |
| Certifications        | BIS, RoHS, ISO               |

### PHYSICAL

|                      |                       |
|----------------------|-----------------------|
| Form Factor          | Mini PC               |
| Dimensions           | 198mm × 200mm × 73mm  |
| Packing Dimensions   | 340mm × 235mm × 105mm |
| Weight               | 110 grams             |
| Housing Material     | Steel                 |
| Housing Finish       | Powder Coated         |
| Housing Colour       | Black                 |
| Net and Gross Weight | 1.59kg, 2.01kg        |

### OPERATING SYSTEM

|                  |                                                                                                                                                                                                                                                                                                                                                                   |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating System | Thinvent® Thinux™ Embedded Linux                                                                                                                                                                                                                                                                                                                                  |
| OS Features      | <p>Chromium and Mozilla Firefox browsers.</p> <p>RDP 10 (RemoteFX, H.264/AVC), Putty and SSH for remote display.</p> <p>Browser based remote management. VNC shadowing.</p> <p>Java, Python and glibc based location application support.</p> <p>LibreOffice and PDF viewer.</p> <p>Multimedia player with MPEG4 support.</p> <p>SIP video and voice over IP.</p> |

## Ordering Information

## PRODUCT CODE

R-i3\_12l-[RAM]-[SSD]-12\_7-[Wireless]-[OS]-[Accessories]

## RAM

4 = 4GB DDR4

8 = 8GB DDR4

16 = 16GB DDR4

32 = 32GB DDR4

32\_32 = 64GB  
DDR4 RAM (2 x  
32GB)16\_16 = 32GB  
DDR4 RAM (2 x  
16GB)8\_8 = 16GB DDR4  
RAM (2 x 8GB)

## SSD

m128 = 128GB

m512 = 512GB

S32 = 32GB MLC

S256 = 256GB

m256 = 256GB

m1024 = 1TB

S128 = 128GB

## Wireless

m = Dual Band WiFi

X = No WiFi

## OS

DOS = DOS

11V = Windows 11 IoT Value

Thinux = Thinux™ Embedded Linux

W\_OS = Without OS

11P = Windows 11 Pro

U = Ubuntu Linux

## Accessories

0 = None

1S = DB9 Serial

Mo = Wired Optical Scroll Mouse

KM = Keyboard and Mouse set

MK = Mechanical Keyboard

[www.thinvent.in](http://www.thinvent.in)[sales@thinvent.in](mailto:sales@thinvent.in)

+91-11-430-77467

 +91-99903-44251

## R&amp;D and Manufacturing

#11 Sports Complex

Salvador Do Mundo

North Goa - 403101, India

## Sales

UGF-10-A Omaxe Gurgaon Mall

Sector 49, Sohna Road

Gurgaon - 122018, India

