



Thinvent Neo R/4 Mini PC

Intel Core i3-1215U processor

6 core, up to 4.4 GHz, 10 MB cache

Dual LAN

32GB DDR4 RAM

1TB SSD

Dual Band WiFi

Thinix Embedded Linux

DB9 Serial

SKU: R-I3_12L-32-M1024-12_7-M-THINUX-1S



Small Powerhouse, Boundless Potential.

Ideal for mission-critical industrial applications

Your compact command centre for demanding environments. The Thinvent® Neo R/4 delivers reliable, fanless computing power where you need it most. Engineered for 24/7 operation, it thrives in spaces where traditional PCs fear to tread.

Why choose the Neo R/4

- Unshakable reliability in a rugged, fanless steel chassis built for harsh conditions.
- Versatile connectivity with dual Gigabit LAN and legacy serial support for seamless integration into existing systems.

- Simplified deployment and management with our pre-installed, secure Thinix™ operating system, ready for your specialised software.
- Effortless remote access and control, allowing you to monitor and manage installations from anywhere.
- A future-proof foundation that balances robust performance with remarkable energy efficiency, reducing total cost of ownership.

From digital signage and kiosks to factory automation and IoT gateways, install confidence with a mini PC built for business.



Thinvent Neo R/4 Mini PC



Specifications

PROCESSING

| | |
|-----------------|---------|
| Generation | 12th |
| Series | i3 |
| Processor Brand | Intel |
| Processor Model | 1215U |
| Cores | 6 |
| Max Frequency | 4.4 GHz |
| Cache | 10 MB |
| Main Memory | 32 GB |
| SSD Storage | 1024 GB |

DISPLAY

| | |
|------|---|
| HDMI | 1 |
| VGA | 1 |

AUDIO

| | |
|-------------|---|
| Speaker Out | 1 |
| Mic In | 1 |

CONNECTIVITY

| | |
|--------------|------------------|
| USB 3.2 | 2 |
| Serial Port | 1 DB9 male RS232 |
| RS485 Option | 1 |

NETWORKING

| | |
|---------------------|-------------------------------|
| Ethernet | 1000 Mbps |
| Ethernet Ports | 2 |
| Wireless Networking | Wi-Fi 5 (802.11ac), dual band |

POWER

| | |
|--------------|--|
| DC Voltage | 12 Volts |
| DC Current | 7 Amps |
| Power Input | 100~275 Volts AC, 50~60 Hz, 1.5 Amps maximum |
| Cable Length | 2 Metre |

ENVIRONMENTAL

| | |
|-----------------------|------------------------------|
| Operating Temperature | 0°C ~ 40°C |
| Operating Humidity | 20% ~ 80% RH, non condensing |
| Certifications | BIS, RoHS, ISO |

PHYSICAL

| | |
|----------------------|-----------------------|
| Form Factor | Mini PC |
| Dimensions | 198mm × 200mm × 73mm |
| Packing Dimensions | 340mm × 235mm × 105mm |
| Weight | 110 grams |
| Housing Material | Steel |
| Housing Finish | Powder Coated |
| Housing Colour | Black |
| Net and Gross Weight | 1.68kg, 2.10kg |

OPERATING SYSTEM

| | |
|------------------|--|
| Operating System | Thinvent® Thinux™ Embedded Linux |
| OS Features | Chromium and Mozilla Firefox browsers. RDP 10 (RemoteFX, H.264/AVC), Putty and SSH for remote display. Browser based remote management. VNC shadowing. Java, Python and glibc based location application support. LibreOffice and PDF viewer. Multimedia player with MPEG4 support. SIP video and voice over IP. |

Ordering Information

| PRODUCT CODE | | | |
|---|--|--------------|--|
| R-i3_12l-[RAM]-[SSD]-12_7-[Wireless]-[OS]-[Accessories] | | | |
| RAM | 4 = 4GB DDR4 64 = 64GB DDR4 | 8 = 8GB DDR4 | 16 = 16GB DDR4 32 = 32GB DDR4 |
| SSD | m128 = 128GB m32 = 32GB m1024 = 1TB S128 = 128GB | | m256 = 256GB m512 = 512GB S32 = 32GB MLC S256 = 256GB |
| Wireless | m = Dual Band WiFi | | X = No WiFi |
| OS | DOS = DOS 11V = Windows 11 IoT Value Thinix = Thinix™ Embedded Linux | | W_OS = Without OS 11P = Windows 11 Pro U = Ubuntu Linux |
| Accessories | 0 = None 1S = DB9 Serial Mo = Wired Optical Scroll Mouse | | KM = Keyboard and Mouse set MK = Mechanical Keyboard |

www.thinvent.in

sales@thinvent.in

+91-11-430-77467

 +91-99903-44251

R&D and Manufacturing
#11 Sports Complex
Salvador Do Mundo
North Goa - 403101, India

Sales
UGF-10-A Omaxe Gurgaon Mall
Sector 49, Sohna Road
Gurgaon - 122018, India

