



# Thinvent Neo R/4 Mini PC

## Intel Core i5-1240P processor

12 core, up to 4.4 GHz, 12 MB cache

## Dual LAN

## 32GB DDR4 RAM (2 x 16GB)

## 256GB SSD

## No WiFi

## Thinix Embedded Linux

## Thinvent Keyboard and Mouse set



SKU: R-I5\_12L-16\_16-S256-12\_5-X-THINUX-KM

Engineered for relentless reliability in the heart of your operation.

### Introducing the Thinvent Neo R/4 Mini PC

This compact industrial powerhouse is built for environments where failure is not an option. Its rugged steel housing and fanless design ensure silent, dust-resistant operation, delivering consistent performance where standard PCs falter.

### Built for demanding industrial applications

- Deploy it as a robust control unit for manufacturing machinery or process automation.
- Utilise its dual LAN ports for creating secure, dedicated network gateways or firewall appliances.

- Run your custom Python or Java applications reliably with the stable Thinix embedded platform.
- Perfect for digital signage, interactive kiosks, or thin client setups in harsh retail or warehouse settings.

Why choose the Neo R/4?

It arrives ready for work, complete with a keyboard and mouse. Its browser-based remote management allows for effortless monitoring and updates from anywhere, minimising downtime. With certified reliability and industrial-grade components, it's the set-and-forget computing core your critical projects deserve.



# Thinvent Neo R/4 Mini PC



## Specifications

### PROCESSING

|                 |         |
|-----------------|---------|
| Generation      | 12th    |
| Series          | i5      |
| Processor Brand | Intel   |
| Processor Model | 1240P   |
| Cores           | 12      |
| Max Frequency   | 4.4 GHz |
| Cache           | 12 MB   |
| Main Memory     | 32 GB   |
| SSD Storage     | 256 GB  |

### DISPLAY

|      |   |
|------|---|
| HDMI | 1 |
| VGA  | 1 |

### AUDIO

|             |   |
|-------------|---|
| Speaker Out | 1 |
| Mic In      | 1 |

### CONNECTIVITY

|         |   |
|---------|---|
| USB 3.2 | 2 |
|---------|---|

### NETWORKING

|                |           |
|----------------|-----------|
| Ethernet       | 1000 Mbps |
| Ethernet Ports | 2         |

### POWER

|              |                                              |
|--------------|----------------------------------------------|
| DC Voltage   | 12 Volts                                     |
| DC Current   | 5 Amps                                       |
| Power Input  | 100~240 Volts AC, 50~60 Hz, 1.5 Amps maximum |
| Cable Length | 2 Metre                                      |

### ENVIRONMENTAL

|                       |                              |
|-----------------------|------------------------------|
| Operating Temperature | 0°C ~ 40°C                   |
| Operating Humidity    | 20% ~ 80% RH, non condensing |
| Certifications        | BIS, RoHS, ISO               |

### PHYSICAL

|                      |                       |
|----------------------|-----------------------|
| Form Factor          | Mini PC               |
| Dimensions           | 198mm × 200mm × 73mm  |
| Packing Dimensions   | 340mm × 235mm × 105mm |
| Weight               | 110 grams             |
| Housing Material     | Steel                 |
| Housing Finish       | Powder Coated         |
| Housing Colour       | Black                 |
| Net and Gross Weight | 2.14kg, 2.56kg        |

### ACCESSORIES

|                    |   |
|--------------------|---|
| Keyboard and Mouse | 1 |
|--------------------|---|

### OPERATING SYSTEM

|                  |                                                                                                                                                                                                                                                                                                                                                                   |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating System | Thinvent® Thinux™ Embedded Linux                                                                                                                                                                                                                                                                                                                                  |
| OS Features      | <p>Chromium and Mozilla Firefox browsers.</p> <p>RDP 10 (RemoteFX, H.264/AVC), Putty and SSH for remote display.</p> <p>Browser based remote management. VNC shadowing.</p> <p>Java, Python and glibc based location application support.</p> <p>LibreOffice and PDF viewer.</p> <p>Multimedia player with MPEG4 support.</p> <p>SIP video and voice over IP.</p> |

## Ordering Information

## PRODUCT CODE

R-i5\_12l-[RAM]-[SSD]-12\_7-[Wireless]-[OS]-[Accessories]

## RAM

**4** = 4GB DDR4**8** = 8GB DDR4**16** = 16GB DDR4**32** = 32GB DDR4**32\_32** = 64GB  
DDR4 RAM (2 x  
32GB)**16\_16** = 32GB  
DDR4 RAM (2 x  
16GB)**8\_8** = 16GB DDR4  
RAM (2 x 8GB)

## SSD

**m128** = 128GB**m512** = 512GB**S32** = 32GB MLC**S256** = 256GB**m256** = 256GB**m1024** = 1TB**S128** = 128GB

## Wireless

**m** = Dual Band WiFi**X** = No WiFi

## OS

**DOS** = DOS**11V** = Windows 11 IoT Value**Thinux** = Thinux™ Embedded Linux**W\_OS** = Without OS**11P** = Windows 11 Pro**U** = Ubuntu Linux

## Accessories

**0** = None**1S** = DB9 Serial**Mo** = Wired Optical Scroll Mouse**KM** = Keyboard and Mouse set**MK** = Mechanical Keyboard[www.thinvent.in](http://www.thinvent.in)[sales@thinvent.in](mailto:sales@thinvent.in)

+91-11-430-77467

 +91-99903-44251

## R&amp;D and Manufacturing

#11 Sports Complex

Salvador Do Mundo

North Goa - 403101, India

## Sales

UGF-10-A Omaxe Gurgaon Mall

Sector 49, Sohna Road

Gurgaon - 122018, India

