



Thinvent Neo R/4 Mini PC

AMD Ryzen 5 7430U processor

6 core, up to 4.3 GHz, 16 MB cache

64GB DDR4 RAM (2 x 32GB)

512GB SSD

Dual Band WiFi

Thinix Embedded Linux

Thinvent Keyboard and Mouse set

SKU: R-R5_7-32_32-M512-19_3-M-
THINUX-KM



Powerfully compact, effortlessly professional: the Neo R/4 Mini PC.

Built for the modern workspace, this tiny powerhouse delivers the performance you need without taking up precious desk space. Powered by a six-core AMD Ryzen™ processor, it handles demanding business applications, multitasking, and multimedia playback with remarkable smoothness.

Why choose this mini PC for your business or industrial setup?

- Space-saving design: its compact steel chassis fits neatly behind a monitor or in tight control panels, freeing your desk for what matters.
- All-in-one convenience: included keyboard, mouse, and pre-installed Thinix™ Embedded Linux mean you're ready to work straight out of the box.
- Reliable remote access: with RDP 10, VNC shadowing, and SSH support, you can securely manage systems from anywhere, ideal for IT professionals and remote teams.

- Versatile connectivity: dual-band Wi-Fi, Gigabit Ethernet, and multiple USB ports let you connect peripherals, displays, and networks effortlessly.
- Software-ready: comes with Chromium and Firefox browsers, LibreOffice for documents, a multimedia player, and support for Java, Python, and SIP VoIP – perfect for point-of-sale, digital signage, or office productivity.

Built with a robust powder-coated steel housing and certified to BIS and RoHS standards, the Neo R/4 is engineered for continuous operation in demanding environments.

Whether you're upgrading an office, building a kiosk, or deploying thin clients, this mini PC offers a silent, low-power, and professional solution that simply works.



Thinvent Neo R/4 Mini PC



Specifications

PROCESSING

Generation	7000 Series
Series	Ryzen 5
Processor Brand	AMD
Processor Model	7430U
Cores	6
Max Frequency	4.3 GHz
Cache	16 MB
Main Memory	64 GB
SSD Storage	512 GB

DISPLAY

HDMI	1
VGA	1

AUDIO

Speaker Out	1
Mic In	1

CONNECTIVITY

USB 3.2 Gen 1	2
USB 2.0	2

NETWORKING

Ethernet	1000 Mbps
Wireless Networking	Wi-Fi 5 (802.11ac), dual band

POWER

DC Voltage	19 Volts
DC Current	3 Amps
Power Input	100~240 Volts AC, 50~60 Hz, 1.5 Amps maximum
Cable Length	2 Metre

ENVIRONMENTAL

Operating Temperature	0°C ~ 40°C
Operating Humidity	20% ~ 80% RH, non condensing
Certifications	BIS, RoHS, ISO

PHYSICAL

Form Factor	Mini PC
Dimensions	198mm × 200mm × 73mm
Packing Dimensions	340mm × 235mm × 105mm
Weight	110 grams
Housing Material	Steel
Housing Finish	Powder Coated
Housing Colour	Black
Net and Gross Weight	1.68kg, 2.10kg

ACCESSORIES

Keyboard and Mouse	1
--------------------	---

OPERATING SYSTEM

Operating System	Thinvent® Thinux™ Embedded Linux
OS Features	Chromium and Mozilla Firefox browsers. RDP 10 (RemoteFX, H.264/AVC), Putty and SSH for remote display. Browser based remote management. VNC shadowing. Java, Python and glibc based location application support. LibreOffice and PDF viewer. Multimedia player with MPEG4 support. SIP video and voice over IP.

Ordering Information

PRODUCT CODE

R-r5_7-[RAM]-[SSD]-19_3-[Wireless]-[OS]-[Accessories]

RAM

4 = 4GB DDR4**8** = 8GB DDR4**16** = 16GB DDR4**32** = 32GB DDR4**32_32** = 64GB
DDR4 RAM (2 x
32GB)**16_16** = 32GB
DDR4 RAM (2 x
16GB)**8_8** = 16GB DDR4
RAM (2 x 8GB)

SSD

m128 = 128GB**m512** = 512GB**S32** = 32GB MLC**S256** = 256GB**m256** = 256GB**m1024** = 1TB**S128** = 128GB

Wireless

m = Dual Band WiFi**X** = No WiFi

OS

DOS = DOS**11V** = Windows 11 IoT Value**Thinux** = Thinux™ Embedded Linux**W_OS** = Without OS**11P** = Windows 11 Pro**U** = Ubuntu Linux

Accessories

0 = None**1S** = DB9 Serial**Mo** = Wired Optical Scroll Mouse**KM** = Keyboard and Mouse set**MK** = Mechanical Keyboardwww.thinvent.insales@thinvent.in

+91-11-430-77467

 +91-99903-44251

R&D and Manufacturing

#11 Sports Complex

Salvador Do Mundo

North Goa - 403101, India

Sales

UGF-10-A Omaxe Gurgaon Mall

Sector 49, Sohna Road

Gurgaon - 122018, India

