



Thinvent® Neo S Thin Client, Intel® Processor N150 (4 core, up to 3.6 GHz, 6 MB cache), 16GB DDR4 RAM, 32GB SSD + 32 GB MLC SSD, 19V 3A Adapter, No WiFi, Thinux™ Embedded Linux, Thinvent® Keyboard and Mouse set

SKU: [S150-150-16-m32_S32-19_3-X-Thinux-KM](#)

Processing

Cores	4
Max Frequency	3.6 GHz
Cache	6 MB
Main Memory	16 GB
SSD Storage	32 GB

Display

HDMI 2.0	1
DisplayPort	1
VGA	1

Audio

Speaker Out	1
Mic In	1

Connectivity

USB 3.2 Gen 2x1	2
USB 2.0	2
Serial Port	1 DB9 male RS232
Parallel Port	1 DB25 female IEEE 1284

Networking

Ethernet	1000 Mbps
----------	-----------

Power

DC Voltage	19 Volts
DC Current	3 Amps
Power Input	100~240 Volts AC, 50~60 Hz, 1.5 Amps maximum
Cable Length	2 Metre

Environmental

Operating Temperature	0°C ~ 40°C
Operating Humidity	20% ~ 80% RH, non condensing
Certifications	BIS, RoHS, ISO

Physical

Dimensions	204mm × 186.5mm × 53.5mm
Packing Dimensions	340mm × 235mm × 105mm
Housing Material	Steel
Housing Finish	Power Coating
Housing Colour	Black
Net and Gross Weight	1.53kg, 1.95kg

Accessories

Keyboard and Mouse	1
--------------------	---

Operating System

Operating System	Thinvent® Thinux™ Embedded Linux
OS Features	Chromium and Mozilla Firefox browsers. RDP 10 (RemoteFX, H.264/AVC), Putty and SSH for remote display. Browser based remote management. VNC shadowing. Java, Python and glibc based location application support. LibreOffice and PDF viewer. Multimedia player with MPEG4 support. SIP video and voice over IP.