



# Thinvent Treo Mini PC

## Intel Core i3-1215U processor

6 core, up to 4.4 GHz, 10 MB cache

## Dual LAN

16GB DDR4 RAM (2 x 8GB)

256GB SSD

No WiFi

Thinux Embedded Linux



SKU: TREO-I3\_12L-8\_8-M256-12\_7-X-THINUX-0

Unmatched Reliability, Proudly Engineered in India.

### Introducing the Thinvent Treo Mini PC

This industrial-grade powerhouse is built from the ground up for demanding environments. Forget fragile plastic casings; its solid aluminium chassis ensures superior durability and efficient heat dissipation, keeping your operations running cool and stable.

### Ideal for a Connected Future

- Deploy effortlessly in digital signage, kiosks, or interactive displays with robust dual LAN connectivity.
- Leverage its embedded Linux OS for secure, low-maintenance operation in thin-client setups or dedicated control panels.

- Enjoy versatile remote management and support for a wide range of productivity and development tools right out of the box.

### Built to Your Vision

We understand that your brand is unique. For larger projects, we offer customisation in colours and design, allowing this resilient computer to integrate seamlessly into your specific application and corporate identity.

Choose the Treo Mini PC for a robust, dependable, and proudly Indian computing solution that works as hard as you do.



# Thinvent Treo Mini PC



## Specifications

### PROCESSING

|                 |         |
|-----------------|---------|
| Generation      | 12th    |
| Series          | i3      |
| Processor Brand | Intel   |
| Processor Model | 1215U   |
| Cores           | 6       |
| Max Frequency   | 4.4 GHz |
| Cache           | 10 MB   |
| Main Memory     | 16 GB   |
| SSD Storage     | 256 GB  |

### DISPLAY

|      |   |
|------|---|
| HDMI | 1 |
| VGA  | 1 |

### AUDIO

|                   |   |
|-------------------|---|
| Speaker Out       | 1 |
| Mic In            | 1 |
| Front Speaker Out | 1 |
| Front Mic In      | 1 |

### CONNECTIVITY

|               |   |
|---------------|---|
| USB 3.2       | 2 |
| Front USB 2.0 | 3 |
| RS485 Option  | 1 |

### NETWORKING

|                |           |
|----------------|-----------|
| Ethernet       | 1000 Mbps |
| Ethernet Ports | 2         |

### POWER

|              |                                              |
|--------------|----------------------------------------------|
| DC Voltage   | 12 Volts                                     |
| DC Current   | 7 Amps                                       |
| Power Input  | 100~275 Volts AC, 50~60 Hz, 1.5 Amps maximum |
| Cable Length | 2 Metre                                      |

### ENVIRONMENTAL

|                       |                              |
|-----------------------|------------------------------|
| Operating Temperature | 0°C ~ 40°C                   |
| Operating Humidity    | 20% ~ 80% RH, non condensing |
| Certifications        | BIS, RoHS, ISO               |

### PHYSICAL

|                      |                            |
|----------------------|----------------------------|
| Form Factor          | Mini PC                    |
| Dimensions           | 199.5mm × 181.5mm × 29.5mm |
| Packing Dimensions   | 224mm × 319mm × 85mm       |
| Housing Material     | Aluminium                  |
| Housing Finish       | Powder Coated              |
| Housing Colour       | Black                      |
| Net and Gross Weight | 1.49kg, 1.71kg             |

### ACCESSORIES

|            |   |
|------------|---|
| VESA Mount | 1 |
|------------|---|

### OPERATING SYSTEM

|                  |                                                                                                                                                                                                                                                                                                                                                                   |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating System | Thinvent® Thinux™ Embedded Linux                                                                                                                                                                                                                                                                                                                                  |
| OS Features      | <p>Chromium and Mozilla Firefox browsers.</p> <p>RDP 10 (RemoteFX, H.264/AVC), Putty and SSH for remote display.</p> <p>Browser based remote management. VNC shadowing.</p> <p>Java, Python and glibc based location application support.</p> <p>LibreOffice and PDF viewer.</p> <p>Multimedia player with MPEG4 support.</p> <p>SIP video and voice over IP.</p> |

## Ordering Information

## PRODUCT CODE

Treo-i3\_12l-[RAM]-[SSD]-12\_7-[Wireless]-[OS]-[Accessories]

## RAM

4 = 4GB DDR4

8 = 8GB DDR4

16 = 16GB DDR4

32 = 32GB DDR4

32\_32 = 64GB  
DDR4 RAM (2 x  
32GB)16\_16 = 32GB  
DDR4 RAM (2 x  
16GB)8\_8 = 16GB DDR4  
RAM (2 x 8GB)

## SSD

m128 = 128GB

m256 = 256GB

m512 = 512GB

m1024 = 1TB

## Wireless

m = Dual Band WiFi

X = No WiFi

## OS

DOS = DOS

W\_OS = Without OS

11V = Windows 11 IoT Value

11P = Windows 11 Pro

Thinix = Thinix™ Embedded Linux

U = Ubuntu Linux

## Accessories

0 = None

KM = Keyboard and Mouse set

MK = Mechanical Keyboard

Mo = Wired Optical Scroll Mouse

[www.thinvent.in](http://www.thinvent.in)[sales@thinvent.in](mailto:sales@thinvent.in)

+91-11-430-77467

 +91-99903-44251

## R&amp;D and Manufacturing

#11 Sports Complex

Salvador Do Mundo

North Goa - 403101, India

## Sales

UGF-10-A Omaxe Gurgaon Mall

Sector 49, Sohna Road

Gurgaon - 122018, India

