



Features:

- Powerful, cost effective thin client for both stand-alone and server based operation.
- **Windows 10 IoT Enterprise OS:** The latest embedded OS from Microsoft, providing Windows OS features in an embedded footprint.
- Internet Explorer, Firefox and Chrome **Web Browsers** with **PDF, Flash, Java** and multimedia plugins.



- Powerful **media player** for digital signage applications. Supports **H.264, MPEG2**, streaming, etc.
- Complete desktop experience – office suite, VoIP and chat client, video-conferencing, etc.



- **RDP, ICA** and **VNC** protocols for Remote Desktop connectivity to Windows XP, 7, 8, 10, Windows Server 2008 and 2012. Printer, disk and sound forwarding.



- **VDI Support:** Microsoft RemoteFX and HyperV, Citrix XenServer, VmWare View



- Support for all popular printers, scanners and multi-functionals. Both local and server based printing.
- Biometric and smart card based authentication.
- RFID, bar code scanner, magnetic stripe and thermal printer support for Point-of-Sale applications.
- Remote Management Suite with browser based administration from any computer. VNC shadowing, SNMP and WMI support.
- Locally install and run your Windows, Java and .NET applications.
- Suitable for **Digital Signage, Point of Sale, Thin Client** and **Kiosk** applications.



Compact product with full legacy port support. Suitable for POS and thin client.

Hardware Specifications

Processor	Intel 2.41 GHz Dual Core processor Hardware graphics acceleration
Memory	DDR3 2 GB. Expandable to 8 GB.
Storage	32 GB SATA Flash. Expandable to 1 TB. Supports SATA 2.5" HDD.
Display	Up to 1920 × 1200, 32-bit colour
Networking	10/100/1000 Mbps Ethernet Port 802.11 b/g/n WLAN (Optional) PPP dialup for GPRS, CDMA, 3G. PPPoE for ADSL. Supports all Indian ISPs and popular USB modems.
I/O Ports	1 × RJ-45 with diagnostic LEDs ⑥ 4 × USB 2.0 ⑤ 1 × USB 3.0 ④ 1 × 15-pin VGA connector ⑦ 1 × HDMI ⑧ 1 × PS/2 Keyboard ② 1 × PS/2 Mouse ③ 3 × 3.5mm Audio Jacks ⑨ 1 × Power Switch
Optional Ports	1 × 9-pin serial 1 × 25-pin serial 1 × 25-pin parallel
Diagnostics	Power On/Off and HDD Activity LEDs
Power Input	220 ~ 240 V AC
Dimensions	240 × 183 × 60 mm
Operating Temperature	0 ~ 35 °C
Net Weight	1.40 kg
Gross Weight	2.30 kg

