



Features:

- Fanless system for noiseless operation
- Ultra low power consumption
- Aesthetic, low profile design (150ml volume)
- Supports a rich set of I/O devices and peripherals
- VESA mounting kit available
- Linux based Thin Client OS - Thinux Embedded Linux
- Firefox and Chrome **Web Browsers** with **PDF, Java** and multimedia plugins.



- Powerful **media player** for digital signage applications. Supports **MPEG4, H.264, MPEG2**, streaming, etc.
- **RDP, ICA** and **VNC** protocols for Remote Desktop connectivity to Windows XP and 7, Windows Server 2008 and 2012 R2. Printer, disk and sound forwarding.



- **VDI** Support: Microsoft RemoteFX and HyperV, Citrix XenServer, VmWare View, vWorkspace and KVM



- Support for all popular printers, scanners and multifunctionals. Both local and server based printing.
- Remote Management Suite with browser based administration from any computer. VNC Shadowing.

Powerful Quad Core ARM based thin client with very low power consumption and hardware accelerated RemoteFX connectivity.

Hardware Specifications

Processor	2.0 GHz, quad core, ARM Cortex A53 750 MHz, penta core, Mali 450MP hardware graphics acceleration
Memory	DDR3 1 GB soldered on-board
Storage	eMMC 8 GB flash soldered onboard
Display	Full HD 1920x1080
Networking	1 Gbps Ethernet Port
I/O Ports	1 xRJ-45 with diagnostic LEDs 2 xUSB 2.0 1 xHDMI 2.0A 1 x15-pin VGA connector (optional) 1 xAudio: Speaker Out 1 xAnalog Video Out 1 xmicroSD card slot

Diagnostic LEDs

Power On/Off

External Power Adapter

Input: 100 ~ 240V AC
Output: 5V/2A DC

Dimensions 80 x80 x12mm

Weight 100gm

Operating Temperature

0 ~ 35°C

